

**Porsche 911E, 911S, 911T (2.2L and 2.4L )  
Group 8 ~ Class A/P, B/P, C/P**

**SVRA Supplemental Regulations**

(revised 1/2013)

**The following cars are covered under these regulations:**

- 1970-1971 Porsche 911E, 911S, 911T (2195cc, SOHC flat 6)
- 1970-1971 Porsche 911E, 911S, 911T (2195cc, SOHC flat 6)
- 1972-1973 Porsche 911E, 911S, 911T (2341cc, SOHC flat 6)

Note: chassis may be updated or backdated to achieve proper specifications.

Engines: .047" (1.2mm) maximum overbore allowed, **stroke must remain standard**

- \*2195cc Bore x stroke.....3.31" x 2.60" (84mm x 66mm) - type 911/20
  - Head & block material.....alloy
  - Carburation.....Bosch fuel injection 38mm or 42mm PED 6KL pump
- 2341cc Bore x stroke.....3.31" x 2.77" (84mm x 70.4mm)
  - Head & block material.....alloy
  - Carburation.....Bosch 6-port fuel injection 29mm, 32mm or 36mm

Transmissions: Porsche transaxle.....4 or 5 speeds, ratios free

Chassis: Steel uni-body coupe, MacPherson struts, torsion bars F & R  
Wheelbase.....89"  
Track dimension, front.....54", +/- 2" Track dimension,  
rear.....53.5", +/- 2"  
Wheels.....7.5" x 15" all tolerances included  
\*(CP) 7" x 15" all tolerances included  
Brakes.....11.1" discs F & 11.4" R

Official weight, measured without driver, at conclusion of race, all tolerances included:

\*2.2L (C/P)...2084#                      2.2L (B/P)...1934#                      2.4L.....(A/P) 2084#

**SVRA approved options (C-Production options marked with\*)**

- \*85mm cylinders & pistons
- \*cast iron sleeves
- \*(2) Weber 40 IDT/IDS or Solex/Zenith 40mm down draft carburetors
- (2) Weber 48 IDA/IDS carbs or PMO equivalent
- \*MSD type electronic ignition, must be triggered from distributor
- Dual ignition distributor
- \*901.351.043/4.20 - front brake caliper
- \*911.351.425/6.01 - "A" caliper
- \*911.351.935/6.00 - 69S caliper
- \*901.352.043/4.20 - rear brake caliper
- \*1978 ~ 911SC - cast iron caliper
- \*1969 ~ 911 front bumper
- \*Anti-sway bars, bushings, torsion bars ~ free
- factory spec fiberglass body parts, ; doors, fenders, bumpers, hood (no reduction in minimum weights)
- Bumpers, headlights, parking lights may be removed (see General Rule & Regulations)
- 1973 or earlier front bumper or rear deck spoiler (duck tail)
- Removal of passenger seat
- \*Wheel arches may be modified only to cover legal tires
- Bosch "High Butterfly" Mechanical Fuel injection (A/P only)
- if no charging system, **add 25# to official weight**

**Specifically prohibited**

- Air dams, lip and unapproved deck spoilers
- Coil-over suspension and remote reservoir shocks
- Tube or semi-tube frame chassis