

SVRA Supplemental Regulations:
(1973) Porsche 911 Carrera RS (2.7L)
(1973-1977) Porsche 911SC (2.7L)

(revised 12/2013)

Group 6 ~ Class GTU

The following cars are covered under these regulations:

1973 Porsche 911RS, 1973-1977 Porsche 911SC (2687cc, SOHC flat 6)

Note: chassis may be updated or backdated to achieve proper specifications. All cars are expected to be race prepared to period racing specifications. No allowance is given for under prepared or "street" cars.

Engines: .047" (1.2mm) maximum overbore allowed, **stroke must remain standard**
(2.7L) 2687cc Bore x stroke.....3.54" x 2.77" (90mm x 70.4mm) – type 911/83
Head & block material.....alloy
Induction.....Bosch K-Jetronic fuel injection or alternate (see below)

Transmissions: Porsche transaxle, type 915/08.....4 or 5 speeds, ratios free

Chassis: Steel uni-body coupe, MacPherson struts, torsion bars F & R
Wheelbase.....89.4"
Track dimension, front.....57.1", all tolerances included Track dimension,
rear.....56.9", all tolerances included
Wheels.....8.5" x 15" F 10" x 15" R all tolerances included
Disc brakes.....282mm(11.1") or 300mm(11.8") F & 290mm(11.4") or 300mm(11.8") R

Official weight, measured without driver, at conclusion of race, all tolerances included: 2234#

SVRA approved options:

Alternate injection: 911.104.008.00 911.110.011.72 (43mm)
911.110.222.72 911.110.012.72 (43mm)
901.110.015.01
Bosch "High Butterfly" Mechanical Fuel injection or Weber 48 IDA/IDS carbs or PMO equivalent
MSD type electronic ignition, must be triggered from distributor
Alternate brakes: 911.351.525.00L 911.351.526.00R
911.352.525.00L 911.352.526.00R
911.351.031.00L 911.351.033.00R
911.352.031.00L 911.352.033.00R
Lockheed p/n CD2270F CD2271R
Ventilated rotors with listed calipers
1977 or earlier front bumper or rear deck spoiler (duck tail)
911RS bodywork
16" wheels in above widths
RS style front valence with oil cooler
fiberglass engine lid

Specifically prohibited (these items are allowed in SVRA Group 10).

electronically programmable fuel injection
tube frame or semi-tube frame chassis
RSR, IROC or IMSA body work
coil over suspension