

Wheel diameter must be as originally fitted unless permitted in (the Spec Sheets).

Tires must be mounted following the manufacturers specification for wheel width.

Bodywork may not be modified beyond period specifications to accommodate approved tires.

SVRA Supplemental Tire Regulations

(Not for Gold Medallion Classes)
(Revision Date 2/2017)

Since tires are a consumable item, SVRA requires tires that are currently available and are of a reasonable age. There is no doubt that modern tire compounds and construction are vastly improved from what was available to competitors when our cars were originally raced.

The intent of these rules is to specify tires that are a reasonable compromise between the tires raced with during the period and what is currently available. Availability in sufficient sizes to maintain equitable tire performance within the Group and Class structure is of primary importance. We are looking for an appropriate level of dry grip for all the cars in a group, to avoid overloading suspension components.

Tires are evaluated by looking at their aspect ratio, tread pattern, carcass design and wear rating. Some tire sizes/brands are acceptable based on true tire diameter and cross-section regardless of the listed aspect ratio.

Some tires listed have been discontinued. These "Legacy" tires remain on the list as long as the age of the existing stock /sizes remain safe for racing use.

Group 1 - Molded Treaded Tires

Minimum aspect ratio of 60, except as listed on the right, tread depth—no less than 2/32" remaining, at all times, over 75% of the tire.

Note: Bodywork may **NOT** be modified beyond period specifications to accommodate listed tires.

Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model Regulations.

Approved Tires:

Avon Racing: 5.0/22-13 & 6.0/22-13 ACB 9 (ACB10 not permitted), CR6ZZ

Goodyear Eagle: 5.50/15 G12 or 12A American Racing: 18/6.0-10 GT

Hoosier: 165/70-10, 185/60-13, 205/60-13, A70-13, 5.0-15; Street TD, Vintage TD,

Speedster

Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 60

For Toyo RA1's and Nitto NT01's, please see page 6 of this document

Group 2 - Molded Treaded Tires

As listed on right or in the latest Monoposto Racing Rules and Regulations.

Monoposto prepared FF's will use Monoposto rules and regulations, please find the rules at monoposto.com

Approved Tires: Monoposto

F1, F2, F3, FB, FSV:

Dunlop: L, M, Post Historic CR65 and CR82

Avon: All-Weather H-003—H009

Grooved slicks that meet the Monoposto Racing and SVRA approved tread standard. A template is available. It is the driver's responsibility to ensure that all grooved slicks meet the approved standard.

Formula Jr: Dunlop L-204 Hard Compound. With other tires will be run as Formula C. **Formula Vee:** Treaded tires per Monoposto Racing Rules.

Monoposto Prepared (FFM, CFM)

Formula Ford Monoposto: Club Ford Monoposto:

See Monoposto tire rules at http://www.monoposto.com/

SVRA prepared Formula Fords will use the SVRA FF Rulebook

Shaving or reducing tread depth of tire by any means other than normal on track driving is prohibited.

SVRA Prepared (FF, CF, PCF)

Formula Ford: Club Ford: Post Club Ford:

Tires: for all classes (Wet or Dry)
Front: Toyo Proxes R888, 185/60R/13
Rear: Toyo Proxes R888, 205/60R/13

Front: Hoosier 135/545-13VFF Rear: Hoosier 165/580-13VFF

Group 3 - Molded Treaded Tires

Minimum aspect ratio of 60, except as listed on the right, tread depth—no less than 2/32" remaining, at all times, over 75% of the tire.

Note: Bodywork may **NOT** be modified beyond period specifications to accommodate listed tires.

Note: Please refer to the "Group 3 Description and Class List" for **Porsche 356** tire limitations and requirements.

Approved Tires:

Avon Racing: 5.0/22-13, & 6.0/22-13, 6.5/23-13 ACB9 (ACB10 not permitted), 185/70-14

(CR6), CR6ZZ

Dunlop: All "L-series, up to 5.50M-13, 14, 15; 135/545-13 & 165/580-13 (9092)" Formula

Ford"

Goodyear Eagle: 5.50/15 G12 or G12A

Hoosier: A70-13, P205/60D-13, 14 (Street TD), up to 5.50-15 (Vintage TD), 185/65-15 &

205/60-15 (Speedster)

Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 60

Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model Regulations.

Tires may not extend beyond the fender opening at the highest point of the tire.

For Toyo RA1's and Nitto NT01's, please see page 6 of this document

Group 4 - Molded Treaded Tires	Approved Tires:				
Tires may not extend beyond the	Modified Catego		1\		
fender opening at the highest point	Blockley	(204 or 484 compou	ına).		
of the tire.	Continental				
	Production Cate	gory:			
			age TD, Hoosier Street	TD or Goo	dyear Blue Streak
	Sports Car Speci	als			
Group 5 - Treaded Tire Group		• • •	eet tires with a suitabl	•	ting.
M/hile constraint and constraint and	· ·	y siicks with SVRA a _l ead patterns are:	pproved tread pattern	S.	
While exact size and aspect ratio are not specified, the entrant must		ead patterns are. nlop: CR-65 and CR-8	R2 tread natterns		
ensure that tire choice is appropriate	•	•	-	l B pattern	are not allowed)
for the car during the eligibility	Avon: All-weather "H-Pattern" (the CR6ZZ radial and B pattern are not allowed) Goodyear: G-12				
period.	A tread pattern template is available. It is the driver's responsibility to ensure any grooved				
	slicks meet the a	approved standard.			
Group 6 - Molded Treaded Tires	Approved Tires:	List per Make and	Model is Listed below	:	
Wheels and Tires:	MAKE	MODEL	PRODUCTION PERIOD	CLASS	TIRE GROUP
	AC Cobra	289		(BP)	a, b
Tires may not extend beyond the					
· · · · · · · · · · · · · · · · · · ·	AC Cobra	427		(AP)	a, b, c
fender opening at the highest point	AMX Sports Coupe	290, 343, 360, 390	1968-69	(BP)	a, b, c a, b
· · · · · · · · · · · · · · · · · · ·			1968-69 1970-72	(BP) (TA)	a, b, c a, b a, b
fender opening at the highest point of the tire.	AMX Sports Coupe AMC	290, 343, 360, 390 Javelin		(BP)	a, b, c a, b
fender opening at the highest point	AMX Sports Coupe AMC AMC Aston Martin Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427	1970-72 1965-67	(BP) (TA) (TA) (BP) (AP)	a, b, c a, b a, b a, b, c a. a, b, c, d
fender opening at the highest point of the tire. Specifically Prohibited for Group 6:	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454	1970-72 1965-67 1968-72	(BP) (TA) (TA) (BP) (AP)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327	1970-72 1965-67 1968-72 1963-67	(BP) (TA) (TA) (BP) (AP) (AP) (BP)	a, b, c a, b a, b a, b, c a. a, b, c a. a, b, c, d a, b, c, d a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6:	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454	1970-72 1965-67 1968-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP)	a, b, c a, b a, b a, b, c a. a, b, c a. a, b, c, d a, b, c, d a, b a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350	1970-72 1965-67 1968-72 1963-67 1968-69	(BP) (TA) (TA) (BP) (AP) (AP) (BP)	a, b, c a, b a, b a, b, c a. a, b, c a. a, b, c, d a, b, c, d a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate	AMX Sports Coupe AMC AMC Aston Martin Chevrolet	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP) (AP) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, d a, b, c, d a, b, c
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Dodge	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP) (AP) (TA) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, d a, b, c, d a, b a, b, c a, b a, b, c a, b a, b a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP) (AP) (TA) (TA) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, c
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP) (AP) (TA) (TA) (TA) (AS) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, c, d a, b a, b, c, d a, b a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, c
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (BP) (AP) (TA) (TA) (TA) (AS) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b a, b, c, d a, b, c, d a, b a, b, c, c a, b a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (BP) (AS) (AS) (AS)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b a, b, c a, b a, b a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 327 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1968-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (BP) (AS) (AS) (TA)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Ford	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302 Mustang BOSS 429	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (AS) (TA) (TA) (AS)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Griffith	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302 Mustang BOSS 429 200/400	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1968-69 1970-72 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (AS) (TA) (TA) (AS)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Ford	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302 Mustang BOSS 429 200/400 XKE	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1968-69 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (TA) (BP) (AS) (TA) (AS) (TA) (AS)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c, d a, b, c, d a, b, c, d a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Griffith Jaguar	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302 Mustang BOSS 429 200/400	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1964-67 1968-69 1970-72 1970-72	(BP) (TA) (TA) (BP) (AP) (AP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (AS) (TA) (TA) (AS)	a, b, c a, b a, b a, b, c a. a, b, c, d a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Ford Griffith Jaguar Mercury Plymouth	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Corvette 350 Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang BOSS 302 Mustang BOSS 429 200/400 XKE Cougar Cougar Valiant, Barracuda	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1968-69 1970-72 1962 + 1966-67 1968-69 1964-67	(BP) (TA) (TA) (BP) (AP) (BP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (TA) (BP) (AS) (TA) (AS) (TA) (AP)	a, b, c a, b a, b a, b, c a, b, c, d a, b, c a, b a, b, c a, b a, b, c a, b
fender opening at the highest point of the tire. Specifically Prohibited for Group 6: Any tire not listed in the Approved Tire list Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model	AMX Sports Coupe AMC AMC Aston Martin Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Chevrolet Dodge Dodge Ferrari Ferrari Ford Ford Ford Ford Ford Griffith Jaguar Mercury	290, 343, 360, 390 Javelin Javelin DB4, DB5 Corvette 396, 427 Corvette 427, 454 Corvette 350 Corvette 350 Corvette 350 Camaro Camaro Dart Challenger 250/275 GT, GTO 365 GTB/4, 375 Falcon Mustang Mustang Mustang Mustang BOSS 302 Mustang BOSS 429 200/400 XKE Cougar Cougar	1970-72 1965-67 1968-72 1963-67 1968-69 1970-72 1967-69 1970-72 1968-72 1968-69 1970-72 1968-69 1970-72 1962 + 1966-67 1968-69	(BP) (TA) (TA) (BP) (AP) (BP) (BP) (AP) (TA) (TA) (TA) (BP) (BP) (AS) (TA) (BP) (AS) (TA) (AS) (TA) (AS) (TA) (AP) (AP) (AP) (AS) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS) (TA) (AS)	a, b, c a, b a, b a, b, c a, b, c, d a, b, c a, b a, b, c a, b a, b, c a, b

Approved DOT Tires:	Pontiac	Firebird	1970-72	(TA)	a, b, c
	Porsche Shelby	904 GTS (2L) GT 350	1965-67	(BP) (BP)	e. a, b
Any Treaded, DOT approved Tires	Shelby	GT 500	1903-07	(AP)	a, b, c
with a UTQG of 100 or greater with	,			()	-, -, -
appropriate Speed Rating and a					
minimum Aspect Ratio of 60	Tire Group (<u>a):</u>	Tire Group	(b):	
	Dunlop M	Carias	Coodyoor	E EO E OO 8: 7 O	0 15 Vintago S.C. Special
For Toyo RA1's and Nitto		.50 & 6.00-15 Vintage S.C. S		275/60D-15 Stre	0-15 Vintage S.C. Special et TD
NT01's, please see page 6 of		25/50D, 225/60D, 245/60D-		26.5/9.5-15 Stre	
this document	TD		Hoosier	25.5/8.5-15 Stre	eet TD (front wheels only)
this document	Tire Group (c)	Tire Group	(4)	
	ille Gloup (<u>v 1</u>	<u>ille dioup</u>	<u> (u)</u>	
		8.00-15 Vintage Sports Car			TD (front wheels only)
		25.5/10.00-15, 27.5/11.00-1	15 Hoosier 2	5.5/8.5-15 Street	TD (front wheels only)
	Street TD				
			Tire Group	(e) May use Gro	up 8 Tire Regulations.
		<u></u>			
Group 7	Approved T	ires:			
	Racing slick	s and treaded racing ti	ires		
	Racing silek	s and treaded racing ti	1163.		
	While exact	size and aspect ratio	are not specified, er	ntrants must er	sure that tire choice is
		e for the car during the	•	ici aries iriase er	isare triat the critical
	app. opacc	, ioi aire ear aan iig	engianity periodi		
Group 8 - Molded Treaded Tires	Approved t	ires:			
Minimum aspect ratio of 45, except	There are no specific sizes listed because of the large diversity of Group 8 cars.				
certain car Make and Models, which	All Group 8 cars must use similar sized tires to what was used in the day, which is pre 1973. Using oversized tires is unacceptable and when in question, SVRA's determination shall be				
have specific tire requirements listed	the final wo		ble and when in que	stion, SVRA's	determination shall be
in their Supplemental Regulations,	the final wo	ra.			
tread depth—no less than 2/32"	Avon: ACRO), ACB10, CR6Z			
remaining, at all times, over 75% of		agle: 5.50/15 G12 or	G12A		
the tire.	_	treet TD & Speedster	OIZA		
Wheels may be of an alternate					
material but must be of period	Any Treade	ed. DOT approved Ti	res with a UTQG o	f 100 or great	er with appropriate
design. They must be the correct	Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 45				
diameter and width as specified	opeca man		ispect nation of 15		
within the Supplemental Regulations	Note: Gro	up 8 must use appro	oved full molded t	readed tires.	regardless of what
of the Make and Model.		on tires a car may ha			_
The mane and model	Sp comean	2 25 a car may no	are to inpeted wit	a piloi la	
Tires may not extend beyond the	For Toyo	RA1's and Nitto	NT01's, nlease s	see page 6 d	of this document
fender opening at the highest point		iz 5 dila ititto	or o, picase .	ce page o t	. This document
of the tire.					
	1				
Group 9	Approved t	ires:			
Group 9 Monoposto Racing Rules and	''	ires: d appropriate slicks an	d trooded tires		

Monoposto Racing Rules and Regulations: monoposto.com

Group 10	Approved Tires:
Group 10 cars are expected to have only period-correct equipment and specifications.	Racing SLICKS. While exact size and aspect ratio are not specified, entrants must ensure that tire choice is appropriate for the car during the eligibility period.
Group 11	Approved Tires:
Group 11 cars are expected to have only period-correct equipment and specifications.	Racing SLICKS. While exact size and aspect ratio are not specified, entrants must ensure that tire choice is appropriate for the car during the eligibility period.
Group 12	GTU, MP1-3 Approved Tires:
Tire sizes must be used as listed in your cars specific racing series. Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within your cars specific racing series	Hoosier: R6/R7 Any Treaded, DOT approved Tires with appropriate Speed Rating
	Note: Group 12 must use above listed approved tires, regardless of what specification tires may have used in a prior racing series.
Tires may not extend beyond the fender opening at the highest point of the tire.	Specifically Prohibited: Slicks Tires

Toyo RA-1 Wear Depths

Full Tread Depth

5/32



3-4/32



2/32





These tires barely meet the spirit of the tire rules at 5/32nds and are more like Slick Tires than a Block or Vintage tread pattern. For 2017 - 4 grooves on these tires will be allowed and 2 grooves showing will be considered illegal, if a car has 2 grooves after a race the car will be disqualified. For 2018 these tires will be removed from the approved tire list.

Nitto NT01 Wear Depths

Full Tread Depth

3/32nds





Legal Illegal

For 2017, 2 grooves will be considered illegal, if a car has 2 grooves after a race the car will be disqualified. For 2018 these tires will be removed from the approved tire list.